

Hesston Swather



Description	EPP	OEM	S/N note	Part Notes
5800				
Compressor	500-222	7020696		York, new w/o clutch LH suction, rotolock head, ER210
Compressor	54-037	7020696		York, reman w/o clutch LH suction, rotolock head, ER210
Clutch	1 CA-300	3317V002		York, new 6.00 dia, 2 grv, 12 volt
Clutch	1 600-208	8045965		York, new 6.70 dia, 1 grv, 12 volt, 3.06 mount distance
Clutch	1 CA-301	702704		York, new 7.00 dia, 2 grv, 12 volt
Expansion Valve	1 904-252	7022304		Flare Inlet 3/8M, Outlet 1/2M, 19" capillary 3/8 coil, 2 ton, ext. equalizer 31" x 1/4FF
Expansion Valve	1 904-202			Flare (use 904-215) Inlet 3/8M, Outlet 1/2M, 12" capillary 3/8 coil, 1-1/2 ton, internal equalizer
Receiver Dryer	804-356	77-22994		4.00 x 6.75, male flare Inlet 3/8 MF x Outlet 3/8 MF, FP
6200				
Compressor	500-222	7020696		York, new w/o clutch LH suction, rotolock head, ER210
Compressor	54-037	7020696		York, reman w/o clutch LH suction, rotolock head, ER210
Clutch	1 CA-300	3317V002		York, new 6.00 dia, 2 grv, 12 volt
Clutch	1 600-208	8045965		York, new 6.70 dia, 1 grv, 12 volt, 3.06 mount distance
Clutch	1 CA-301	702704		York, new 7.00 dia, 2 grv, 12 volt
Expansion Valve	1 904-252	7022304		Flare Inlet 3/8M, Outlet 1/2M, 19" capillary 3/8 coil, 2 ton, ext. equalizer 31" x 1/4FF
Expansion Valve	1 904-202			Flare (use 904-215) Inlet 3/8M, Outlet 1/2M, 12" capillary 3/8 coil, 1-1/2 ton, internal equalizer
Receiver Dryer	804-260	841551		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
6400				
Compressor	500-222	7020696		York, new w/o clutch LH suction, rotolock head, ER210
Compressor	54-037	7020696		York, reman w/o clutch LH suction, rotolock head, ER210
Clutch	1 CA-300	3317V002		York, new 6.00 dia, 2 grv, 12 volt
Clutch	1 600-208	8045965		York, new 6.70 dia, 1 grv, 12 volt, 3.06 mount distance
Clutch	1 CA-301	702704		York, new 7.00 dia, 2 grv, 12 volt
Expansion Valve	1 904-252	7022304		Flare Inlet 3/8M, Outlet 1/2M, 19" capillary 3/8 coil, 2 ton, ext. equalizer 31" x 1/4FF
Expansion Valve	1 904-202			Flare (use 904-215) Inlet 3/8M, Outlet 1/2M, 12" capillary 3/8 coil, 1-1/2 ton, internal equalizer
Receiver Dryer	804-260	841551		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
6600				
Compressor	54-037	7020696		York, reman w/o clutch LH suction, rotolock head, ER210
Compressor	500-222	7020696		York, new w/o clutch LH suction, rotolock head, ER210
Clutch	1 CA-300	3317V002		York, new 6.00 dia, 2 grv, 12 volt
Clutch	1 600-208	8045965		York, new 6.70 dia, 1 grv, 12 volt, 3.06 mount distance
Clutch	1 CA-301	702704		York, new 7.00 dia, 2 grv, 12 volt
Expansion Valve	1 904-252	7022304		Flare Inlet 3/8M, Outlet 1/2M, 19" capillary 3/8 coil, 2 ton, ext. equalizer 31" x 1/4FF
Expansion Valve	1 904-202			Flare (use 904-215) Inlet 3/8M, Outlet 1/2M, 12" capillary 3/8 coil, 1-1/2 ton, internal equalizer
Receiver Dryer	804-356	77-22994		4.00 x 6.75, male flare Inlet 3/8 MF x Outlet 3/8 MF, FP

1: Check illustrations
 2: May require oil change
 3: New, check illustration

Hesston Swather



Description	EPP	OEM	S/N note	Part Notes
8200				
Compressor	CO-9285C			Sanden new with clutch, SD508, #9285 132mm / 5.25 dia, 2 grv, 12 volt, Vertical oring fittings, FG head 5-bolt, Ear mount
Compressor	504-532			Sanden reman with clutch, SD508, #9285 132mm / 5.25 dia, 2 grv, 12 volt, Vertical oring fittings, FG head 5-bolt, Ear mount (500-270)
Clutch	600-394	509285		Sanden new 5.22 dia, 2 grv
Expansion Valve	904-245			Block, oring Inlet 3/8, Outlet 1/2, Suction: in 1/2, out 5/8; (2) 1/4" mtg holes, 1-1/2 ton
Receiver Dryer	804-2020			4.25 x 7.63, male oring Inlet 3/8 MO x Outlet 3/8 MO, SP

1: Check illustrations
2: May require oil change
3: New, check illustration